

Metallized Polypropylene Film Capacitors

Capacitor Range : 0.01uF~10uF

Rated Voltages : 100/250/400/630VDC

Temperature range : -40°C ~ +105°C

Dissipation Factor(DF) : Frequency:1KHz ± 2%, Voltage: <1Vrms

100VDC					250VDC					400VDC				
容量範圍 Cap	尺寸 Size mm			腳距	容量範圍 Cap	尺寸 Size mm			腳距	容量範圍 Cap	尺寸 Size mm			腳距
uF	寬 W	高 H	厚 T	Pitch	uF	寬 W	高 H	厚 T	Pitch	uF	寬 W	高 H	厚 T	Pitch
0.01~0.015	10.5	9.0	6.0	7.5	0.01~0.022	13.0	10.0	6.0	10.0	0.01	13.0	10.0	6.5	10.0
0.022	13.0	10.0	6.0	10.0	0.033~0.047	13.0	10.0	6.5	10.0	0.015	13.0	10.5	6.5	10.0
0.033~0.047	13.0	10.0	6.5	10.0	0.068	13.0	10.5	6.5	10.0	0.022	13.0	11.0	7.5	10.0
0.068	13.0	10.5	6.0	10.0	0.1	13.0	11.0	7.0	10.0	0.033	13.0	11.5	7.5	10.0
0.1	13.0	11.0	7.0	10.0	0.15	18.5	12.0	7.0	15.0	0.047	13.0	12.5	7.5	10.0
0.15	18.5	12.0	7.0	15.0	0.22	18.5	12.5	7.5	15.0	0.068	18.5	12.5	7.5	15.0
0.22	18.5	12.5	7.5	15.0	0.33	18.5	14.5	8.5	15.0	0.1	18.5	13.5	8.0	15.0
0.33	18.5	14.5	8.5	15.0	0.47	18.5	15.5	10.0	15.0	0.15	18.5	15.0	9.5	15.0
0.47	18.5	15.5	10.0	15.0	0.68	26.0	15.0	8.5	22.5	0.22	26.0	15.0	8.0	22.5
0.68	26.0	15.0	8.5	22.5	1.0	26.0	19.5	7.5	22.5	0.33	26.0	16.0	10.0	22.5
1.0	26.0	19.5	7.5	22.5	1.5	26.0	19.5	11.5	22.5	0.47	32.0	18.5	11.5	27.5
1.5	26.0	19.5	11.5	22.5	2.2	32.0	22.0	12.5	27.5	0.68	32.0	20.5	12.5	27.5
2.2	32.0	22.0	12.5	27.5	3.3	32.0	26.0	16.5	27.5	1.0	32.0	24.5	16.0	27.5
3.3	32.0	26.0	16.5	27.5	4.7	32.0	28.0	18.0	27.5	1.5	32.0	29.5	17.0	27.5
4.7	32.0	28.0	18.0	27.5	6.8	37.0	30.0	20.0	32.5	2.2	32.0	31.0	18.0	27.5
6.8	37.0	30.0	20.0	32.5	10	37.0	35.0	24.5	32.5					
10	37.0	35.0	24.5	32.5										

Metallized Polypropylene Film Capacitors

630VDC				
容量範圍 Cap	尺寸 Size mm			腳距
uF	寬 W	高 H	厚 T	Pitch
0.01	13.0	11.0	6.5	10.0
0.015	13.0	11.5	7.0	10.0
0.022	13.0	12.5	8.0	10.0
0.033	18.5	13.0	8.0	15.0
0.047	18.5	14.0	8.5	15.0
0.068	18.5	15.0	9.5	15.0
0.1	26.0	14.5	8.0	22.5
0.15	26.0	15.5	9.5	22.5
0.22	32.0	19.0	12.0	27.5
0.33	32.0	22.0	14.5	27.5
0.47	32.0	24.5	15.5	27.5
0.68	32.0	29.0	16.5	27.5
1.0	32.0	31.0	18.0	27.5