

Double sided metallized polypropylene Film Capacitor

Capacitor Range : 0.00022uF~1.0uF

Rated Voltages : 630/1000/1600/2000VDC

Temperature range : -40 °C to +105 °C

Dissipation Factor(DF) : <=0.001(0.1%) at 1 KHz

630VDC	1000VDC~2000VDC
	

400VDC					630VDC					1000VDC				
容量範圍 Cap	尺寸 Size mm			腳距	容量範圍 Cap	尺寸 Size mm			腳距	容量範圍 Cap	尺寸 Size mm			腳距
uF	寬 W	高 H	厚 T	Pitch	uF	寬 W	高 H	厚 T	Pitch	uF	寬 W	高 H	厚 T	Pitch
0.0027~0.012	10.5	9.0	4.0	7.5	0.00068~0.0056	10.5	9.0	4.0	7.5	0.00047~0.001	10.5	9.0	4.0	7.5
0.015~0.018	10.5	11.0	5.0	7.5	0.0068~0.0082	10.5	11.0	5.0	7.5	0.0012~0.0022	10.5	12.0	6.0	7.5
0.022~0.027	10.5	12.0	6.0	7.5	0.01~0.012	10.5	12.0	6.0	7.5	0.0027~0.0033	10.5	12.0	6.0	7.5
0.01~0.022	13.0	9.0	4.0	10.0	0.0039~0.0082	13.0	9.0	4.0	10.0	0.001~0.0033	13.0	9.0	4.0	10.0
0.027~0.033	13.0	11.0	5.0	10.0	0.01~0.012	13.0	11.0	5.0	10.0	0.0039~0.0047	13.0	11.0	5.0	10.0
0.039~0.047	13.0	12.0	6.0	10.0	0.15~0.018	13.0	12.0	6.0	10.0	0.0056~0.0068	13.0	12.0	6.0	10.0
0.033~0.056	17.5	11.0	5.0	15.0	0.01~0.027	17.5	11.0	5.0	15.0	0.0082~0.015	17.5	11.0	5.0	15.0
0.068~0.082	17.5	12.0	6.0	15.0	0.033~0.047	17.5	12.0	6.0	15.0	0.018~0.022	17.5	13.5	7.5	15.0
0.1~0.12	17.5	13.5	7.5	15.0	0.056	17.5	13.5	7.5	15.0	0.027~0.033	17.5	14.5	8.5	15.0
0.15	17.5	14.5	8.5	15.0	0.068~0.082	17.5	14.5	8.5	15.0	0.039	17.5	16.0	10.0	15.0
0.18~0.22	17.5	16.0	10.0	15.0	0.1	17.5	16.0	10.0	15.0	0.047	17.5	19.0	11.0	15.0
0.27	17.0	19.0	11.0	15.0	0.12	17.5	19.0	11.0	15.0	0.027~0.039	26.5	15.0	6.0	22.5
0.12~0.18	26.5	15.0	6.0	22.5	0.047~0.1	26.5	15.0	6.0	22.5	0.047~0.056	26.5	16.0	7.0	22.5
0.22	26.5	16.0	7.0	22.5	0.12	26.5	17.0	8.5	22.5	0.068	26.5	17.0	8.5	22.5
0.27~0.33	26.5	17.0	8.5	22.5	0.15~0.18	26.5	17.0	8.5	22.5	0.082~0.1	26.5	18.5	10.0	22.5
0.39~0.47	26.5	18.5	10.0	22.5	0.22	26.5	18.5	10.0	22.5	0.12~0.15	26.5	22.0	12.0	22.5
0.56~0.68	26.5	22.0	12.0	22.5	0.27~0.39	26.5	22.0	12.0	22.5	0.1	32.0	18.0	9.0	27.5
0.39~0.47	32.0	18.0	9.0	27.5	0.15~0.27	32.0	18.0	9.0	27.5	0.12~0.15	32.0	20.0	11.0	27.5
0.56~0.68	32.0	20.0	11.0	27.5	0.33~0.39	32.0	20.0	11.0	27.5	0.18~0.22	32.0	22.0	13.0	27.5
0.82	32.0	22.0	13.0	27.5	0.47~0.56	32.0	22.0	13.0	27.5	0.27	32.0	24.5	15.0	27.5
1.0~1.2	32.0	24.5	15.0	27.5	0.68	32.0	24.5	15.0	27.5	0.33	32.0	28.0	14.0	27.5
1.5~1.8	32.0	33.0	18.0	27.5	0.82	32.0	28.0	14.0	27.5	0.39~0.47	32.0	33.0	18.0	27.5
					1.0~1.2	32.0	33.0	18.0	27.5					

Double sided metallized polypropylene Film Capacitor

1600VDC					2000VDC				
容量範圍 Cap	尺寸 Size mm			腳距	容量範圍 Cap	尺寸 Size mm			腳距
uF	寬 W	高 H	厚 T	Pitch	uF	寬 W	高 H	厚 T	Pitch
0.00068~0.0068	17.5	11.0	5.0	15.0	0.00022~0.0027	17.5	11.0	5.0	15.0
0.0082~0.01	17.5	12.0	6.0	15.0	0.0033~0.0047	17.5	12.0	6.0	15.0
0.012~0.015	17.5	13.5	7.5	15.0	0.0056~0.0068	17.5	13.5	7.5	15.0
0.018~0.022	17.5	14.5	8.5	15.0	0.0082	17.5	14.5	8.5	15.0
0.027	17.5	16.0	10.0	15.0	0.01~0.012	17.5	16.0	10.0	15.0
0.033	17.0	19.0	11.0	15.0	0.015	17.5	19.0	11.0	15.0
0.015~0.027	26.5	15.0	6.0	22.5	0.001~0.012	26.5	15.0	6.0	22.5
0.033	26.5	16.0	7.0	22.5	0.015~0.018	26.5	16.0	7.0	22.5
0.039	26.5	17.0	8.5	22.5	0.022	26.5	17.0	8.5	22.5
0.047~0.056	26.5	18.5	10.0	22.5	0.027~0.033	26.5	18.5	10.0	22.5
0.068~0.082	26.5	22.0	12.0	22.5	0.039~0.047	26.5	22.0	12.0	22.5
0.039~0.068	32.0	18.0	9.0	27.5					
0.082~0.1	32.0	20.0	11.0	27.5					
0.12	32.0	22.0	13.0	27.5					
0.15~0.18	32.0	24.5	15.0	27.5					
0.22~0.33	32.0	33.0	18.0	27.5					